

(12) UK Patent Application (19) GB (11) 2 193 425 (13) A

(43) Date of printing by UK Office 10 Feb 1988

(21) Application No 8722822

(22) Date of filing 27 Mar 1986

(30) Priority data

(31) 8508512

(32) 2 Apr 1985

(33) GB

(86) International application data

PCT/GB86/00180 En 27 Mar 1986

(87) International publication data

WO86/05657 En 9 Oct 1986

(51) INT CL* (as given by ISA)

A01M 23/18

(52) Domestic classification (Edition J):

A1M DG

U1S 1023 A1M

(56) Documents cited by ISA

GB A 2116817 US 3624951

US 2692453

DE C 0536590 US 3394487

(58) Field of search by ISA

IPC4 A01M

(71) Applicants

Charles Henry Nicholls,
9 Ashburton Road, Alresford, Hampshire.

Philip James Nicholls,

15 Pont Close, Punnetts Town, Heathfield, East Sussex

(74) Agent and/or Address for Service

Nigel Brooks,
Hill Hampton, East Meon, Nr. Petersfield, Hampshire
GU32 1QN


(72) Inventors

Charles Henry Nicholls

Philip James Nicholls

(54) Animal trap

(57) An animal trap comprises a tunnel-shaped body (1) having a floor (2), two side walls (3, 4), a top (5), an open end (6) and a closed end (7), a treadle (11) pivotally connected to the floor (2) at an open-end part of the treadle (11) for movement between a set position in which it is angled up from the floor (2) and a trip position in which it is at least less steeply angled with respect to the floor (2), a door (16) pivotally connected at a top edge thereof to the top of the body (1) at or close to the open end (6) for downwards swinging movement from a set position extending beneath at least part of the top (5) of the body (1) and a trip position in which it closes the open end (6) of the body (1), a trip rod (29) having one end pivotally connected to the treadle (11) at a position spaced towards the closed-end (7) of the body (1) from the treadle's, pivoted, open-end part and another end slidably connected to the top (5) of the body (1), and a hook (31) integral with the other end of the trip rod (29) engageable with the door (16) to hold it in its set position and disengageable for downwards swinging of the door (16) on movement of the trip rod's other end and its hook (31) from the open end (6) of the body (1) and a previously engaged part of the door (16).



Best Available Copy

GB 2 193 425 A